

04-04-00

PTO/SB/05 (4/98)

Please type a plus sign (+) inside this box → ☐Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

04/03/00

UTILITY
PATENT APPLICATION
TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. YOR000122US1 (8728-370)

First Inventor or Application Identifier Bellamy et al.

Title USER-DEFINED ONLINE INTERACTION METHOD...

Express Mail Label No. EL433927527US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 37]
(preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 12]
4. Oath or Declaration [Total Pages]
- a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY
FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT
IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement ☐ Power of
(when there is an assignee) Attorney
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
(PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other: _____

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____

Prior application information: Examiner _____

Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied
under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by
reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

Name	Frank Chau				
Address	F. Chau & Associates, LLP 1900 Hempstead Turnpike, Suite 501				
City	East Meadow	State	New York	Zip Code	11554
Country	USA	Telephone	516-357-0091	Fax	516-357-0092

Name (Print/Type)	Frank Chau	Registration No. (Attorney/Agent)	34,136
Signature		Date	4/3/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any
comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office,
Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents,
Box Patent Application, Washington, DC 20231.

Assistant Commissioner for Patents
Washington, D.C. 20231
Sir:

00/30/00



ATTORNEY DOCKET:YOR000122US1 (8728-370)

Date: April 3, 2000

Express Mail Label: EL433927527US

Date of Deposit: April 3, 2000

Transmitted herewith for filing is one Patent Application of:

Inventors: Rachel K. E. Bellamy, Jason Ellis, Thomas D. Erickson, Wendy A. Kellogg,
Mark Laff, Peter K. Malkin, John T. Richards

For: USER-DEFINED ONLINE INTERACTION METHOD AND DEVICE

Enclosed are: [X] 30 sheets of specification; [X] 1 sheet(s) of Abstract; [X] 6 sheet(s) of claims; [X] 12 sheet(s) of drawing(s);

- [] An assignment of the invention to International Business Machines Corporation with Recordation Form.
- [] Declaration and Power of Attorney.
- [] A certified copy of a _____ application, from which priority under Title 35 USC §119 is claimed.
- [] Associate Power of Attorney.

The filing fee has been calculated as shown below:

(Col. 1) (Col. 2)

OTHER THAN A SMALL ENTITY

FOR:	NO. FILED	NO. EXTRA
BASIC FEE		
TOTAL CLAIMS	32 -20 =	12
INDEP CLAIMS	3-3 =	0
___ MULTIPLE DEPENDENT CLAIMS PRESENTED		

RATE	FEE
	\$690.00
X \$18 =	216.00
X \$78 =	0
+ 260 =	
TOTAL	\$906.00

If the difference in Col. 1 is less than zero, enter "0" in Col. 2.

- [] A check in the amount of \$_____ to cover the [] filing fee(s), [] recording fee is enclosed.
- [X] Please charge my Deposit Account No. 50-0510/IBM (Yorktown Heights) in the amount of \$906.00.
- [X] The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 50-0510/IBM (Yorktown Heights). A duplicate copy of this sheet is enclosed.
- [X] Any additional filing fees required under 37 CFR 1.16.
- [X] Any patent application processing fees under 35 CFR 1.17.

Respectfully submitted,

By: _____

Frank Chau
Registration No. 34,136
Attorney for:
IBM Corporation
Intellectual Property Law Dept.
P.O. Box 218
Yorktown Heights, NY 10598

Please address all
correspondence to:
F. CHAU & ASSOCIATES, LLP
1900 Hempstead Tpke., Suite 501
East Meadow, NY 11554
Tel: (516) 357-0091
Fax: (516) 357-0092

CERTIFICATION UNDER 37 C.F.R. §1.10

I hereby certify that this Application transmittal and documents referred to as enclosed are being deposited with the United States Postal Service on this date April 3, 2000 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EL433927527US addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

Frank Chau

USER-DEFINED ONLINE INTERACTION METHOD AND DEVICE

Background of the Invention

1. Field of the Invention

The present invention is related to a device and method for online user
5 interaction; particularly, a device and method for facilitating user-defined structured
forms of online conversation.

2. Discussion of Related Art

Despite the continued explosive growth in the popularity and use of the Internet,
support for social interaction in online communities remains limited and primitive. In
10 particular, no online support is available for structured styles of interactions (**genres**)
online, which can be defined by, and modified by the end-users - even during usage; and
which enable user-defined rules of enforcement.

To better understand genres, consider the following example of a structured
interaction. In a lecture concerned with computer-mediated communication, there is a
15 speaker and an audience of spectators. When the lecture begins - somehow signaled by
the speaker - all spectators fall silent to listen to the speaker present her lecture.
Assuming that all questions are to be held to the end of the lecture, the speaker is never
interrupted. Once the speaker has finished her presentation - another event somehow
signaled by the speaker - spectators are able to ask questions. To do so, a given spectator

must raise his hand and wait to be called upon by the speaker; no talking out of turn is allowed. Once a given spectator is selected by the speaker, he can ask his question, the content and presentation of which should be short. Once asked, the speaker responds to the question, the presentation here being arbitrarily long. Following her answer, the speaker, then either accepts another question, or ends the lecture. Note that the roles present in this lecture interaction include: the speaker (one particular user), one or more spectators (the other active users), and, when selected, a questioner (one of the spectators, one who "raised his hand" and as then been called upon by the speaker). Note also how the "speaker" and "spectators" always refer to the same particular individuals, while the "questioner" changes, often being undefined (i.e., when no one is asking a question). If a spectator was to shout out a question at an inappropriate time, the speaker could merely chide the offending spectator, telling him to wait for the question section, or, if the spectator was truly abusive, the speaker could have the offending spectator removed from the premises.

For further detail on genres, see Thomas Erickson "Social Interaction on the Net: Virtual Community as Participatory Genre," accessible via URL:
http://www.pliant.org/personal/Tom_Erickson/VC_as_Genre.html. Examples of online interaction facilities follow:

FTP allows online users "*anonymous*" - to have access to a collection of documents; one or more users being authorized to add documents to the collection. No other styles of interaction are definable by the users. (See Ed Krol, *The Whole Internet Catalog*. O'Reilly and Associates, Inc. Sebastopol, CA. 1992 for details).

00000000 "00000000" 00000000

5 **NNTP** or network news, provides a venue in which users can asynchronously post messages and responses into administered news groups (i.e., predefined groups of messages which are meant to relate to specified topic, e.g., all articles in alt.sport.soccer should deal with soccer). Only loosely structured forms of interaction are provided, e.g., query-and-respond, which are not then enforced. No other styles of interaction are user definable.

10 **Internet Relay Chat (IRC)** is similar to NNTP in that it allows users to post messages and responses to each other in predefined topic areas - called channels in IRC. The main difference with IRC is that the interactions are synchronous rather than asynchronous as in NNTP. Just as with NNTP, IRC does not enable users to define structured forms of interaction which include rules of enforcement.

15 **Loom**, a visualization tool for Usenet (NNTP) news groups, provides a technique for displaying the emotional mood (e.g., hostile, happy) of an NNTP-based online community (e.g., a Usenet newsgroup) by analyzing the content of its interactions. Although this utility can analyze online interactions and provide a graphical representation of aspects of the interactions, it does not provide a way for users to define structured styles of interaction. (See Judith Donath et al. "Visualizing Conversation" published in the *Journal of Computer Mediated Conversation*. Volume 4, number 4, June 1999)

20 **Babble** provides dynamic indicators of the presence and activity of all operational users with respect to the available topics (i.e., discussion areas created by the users).

These indicators are computed using the activities of the participants (e.g., connections, postings and topic switches). Although lightly structured styles of interaction are frequently adopted (e.g., interaction in the "-Commons Area-" is informal conversation, while interaction in the "Babble Problems" topic consists of serious question/answer dialogs), no way is provided for users to formally specify structured styles of interaction and then have them enforced. (See Thomas Erickson, et al. "Socially Translucent Systems: Social Proxies, Persistent Conversation, and the Design of 'Babble.'" published in *Human Factors in Computing Systems: The Proceedings of CHI '99*. ACM Press, 1999.)

Online games, like chess and bridge (e.g., Chessmaster 6000 by Mindscape, Inc.), provide structured and enforced styles of interaction, but not ones that (1) can be defined by the users, the rules all being predefined; (2) that can have the rules changed by the users *during* a game (e.g., "A queen can leap from anywhere to anywhere"); and (3) that include user defined rules of enforcement.

Coordinator, a method of structuring human communications, provides an electronic mail-based system that allows users to structure conversations and track tasks. For example, a typical interaction begins with a "Request" message from person A to person B, requesting something from person B by a certain date. This e-mail note asks Person B to respond with a "Promise" message (promising to perform the action), with a "Decline" message (declining to perform the action), or with a "Counteroffer" message (offering to perform the action by a different date or to perform a different action). If B promises to do the action, then a typical conversation might continue with B, eventually

during use. And, a need exists for dynamically updated genre state indicators (graphical representations) whose graphic behaviors are defined by the end-users.

Summary of the Invention

In accordance with the aforementioned needs, the present invention is directed to
5 a method, system and apparatus enabling user-defined structured styles of interaction,
genres, online. The present invention enables users to define their own genres, (such as a
debate genre in which users can participate in a formal debate online), including rules of
interaction, which specify what users of a given genre can do and when, as well as rules
of enforcement, which specify what users are not supposed to do, when, and what
10 happens when they break the rules. Genre definitions also can include the specification
of roles (e.g., the speaker in a lecture genre); parameters (e.g., Max_Post_Length, the
maximum allowable length of each posting); and states (e.g., the Presentation_period in a
lecture genre). Genres can be created from scratch, or by first retrieving a previously
defined genre (e.g., "Basic Lecture"), modifying it (e.g., adding rules), and then saving it
15 under a new name (e.g., "6th-Grader Lecture"). The present invention also allows users
to modify and delete these genre definitions off-line, i.e., when no instances are in use.

The present invention allows users to modify the rules of a given genre while they
are using an instance of it. For example, if users of a debate genre find that the
maximum allowable length of postings is too short, they can increase this value. Users
20 can also add rules, such as to allow users of a lecture genre request clarifications at any
time, even during the speaker's formal presentation period. Users are able to have these
changes saved to permanently change the given genre's definition.

Further, a user can change the genre of an instance in which they are participating *while* they are participating. For example, if the speaker of an instance of a lecture genre finds that the question and answer period is centered around a single contentious point, she could change the genre of the instance from lecture to debate.

5 The present invention also provides dynamically updated graphical representations of the state of genre instances. These graphical representations show both who is doing what (e.g., the user represented by the yellow dot is asking a question); as well as what particular users should be doing (e.g., providing an indication of whose turn it is to speak in a debate genre). Methods are also provided to show when a user
10 violates one or more rules (e.g., indicating who has spoken out of turn). These indicators can also provide action history (e.g., the interruption indicator for a given user growing larger each time the given user interrupts). Finally, these graphic representations allow users to interact with genre instances using graphic user interface techniques (e.g., allowing participants of a debate genre instance to change sides by dragging and
15 dropping the icon which represents them from the region representing the "For" point of view, to the region representing the "Against" point of view).

A method according to the present invention provides user-defined structured interaction online. The method comprising the steps of: defining an interaction genre; creating an operational instance of the genre, said instance being initialized to a
20 predetermined state; monitoring input from online users operatively connected to said instance; updating a state of the instance and responding to user's requests if said input

satisfies a criteria set by the instance's interaction rules; and broadcasting the updated state to all online users operatively connected to the instance.

According to a preferred embodiment of the present invention, a computer-based medium having stored programs readable by a computer is provided for causing the computer to execute method steps for facilitating interaction among a plurality of users operatively connected to the computer, the method comprising the steps of: receiving requests from the plurality of users to participate in an interactive session; registering said users by storing user identifications and passwords of respective users; storing said identifications and passwords in a user database; authorizing said users as participants in the interactive session upon receiving a clearance signal from the computer; setting parameters and rules governing the interactive session and informing the participants of the parameters and rules; monitoring inputs from the participants during the interactive session; and enforcing penalties upon participants violating said rules.

Brief Description of the Drawings

These, and further objects, advantages, and features of the invention will be more apparent from the following detailed description of preferred embodiments and the appended drawings wherein:

Figure 1 shows a network topology employed according to a preferred embodiment of the present invention;

Figure 2 is a block diagram of a server according to the present invention;

Figure 3 is a flow diagram of an exemplary process of the server logic according to the present invention;

Figure 4 is a flow diagram of a process of a genre server handler according to the present invention;

5 Figure 5 is a flow diagram of a process of a registration handler according to the present invention;

Figure 6 is a flow diagram of a process of an instance handler according to the present invention;

10 Figure 7 is a block diagram of major components of a client according to the present invention;

Figure 8 is a flow diagram of a process of a client logic according to the present invention;

Figure 9 is a flow diagram of a process of a genre client handler according to the present invention;

15 Figure 10 shows an exemplary graphic representation of a lecture;

Figure 11 shows another exemplary graphic representation of a lecture;

Figure 12 shows a graphic representation of a debate; and

Figure 13 shows a graphic representation of a roundtable discussion.

Detailed Description of Preferred Embodiments of the Invention

A method and device according to the present invention support structured styles of interaction, or **genres** online. The interactions referred to are those that take place via networked services, including, but not limited to networked client/server services. As
5 previously discussed, Internet Relay Chat (IRC) is one form of online interaction which enables users to post messages in one of several channels, each channel being a section related to a particular topic. Postings on the channel are seen by all other participates interacting with the same channel.

According to a preferred embodiment of the present invention, each channel of
10 the IRC is treated as an instance of a genre. As such, interactions of the participants in the channel are governed by the interaction rules of the given genre, and violations of the rules dealt with using the genre's enforcement rules. For example, in a channel which is an instance of a debate genre, the order and length of the participant's postings are governed by the interaction rules of the debate genre, and interruptions are handled using
15 the debate genre's enforcement rules.

The present invention provides dynamic genre state indicators including graphic or iconic representations which indicate both the genre active in the current channel (e.g., a lecture) and its state (e.g., who is the speaker; who are the spectators and whether the speaker is still in the middle of their formal presentation or whether the question and
20 answer period has begun).

Network (1000) is an electronic communication network. Examples of network (1000) include, but are not limited to, the Internet, the World Wide Web, an Internet and local area networks (LANs).

Each of clients (1202-1060) is a computer device or a computer workstation.

5 Examples of clients (1020 - 1060) include, but are not limited to, an IBM ThinkPad running Windows 95, or Apple's Power MacIntosh running MacOS 8.5.6. Clients also include network-connectable mobile (i.e. portable) devices such as that sold under the trademark WorkPad by IBM, as well as smart cellular telephones (e.g., devices which can act as a cellular telephone as well as run network applications, like e-mail) sold under
10 the trademark Nokia 9000i by Nokia.

Figure 2 shows a block diagram of major components of server (1010), which hosts the online conversation environment. The server (1010) preferably includes a CPU (2000), a network interface (2005), memory (2020) such as RAM, and a storage device (2010) such as a disk or DASD. According to an embodiment of the present invention,
15 Genre Server logic is used to operate the server and is preferably embodied as computer executable code that is loaded remotely over the network via the network interface (2005), or locally from permanent optical CD-ROM, magnetic storage such as disk, or DASD (2010) into memory (2020) for execution by CPU (2000). Network
20 communications to and from the server are made through the network interface (2005), communication types include but are not limited to Ethernet, token-ring, and wireless, such as via RF or IR. The memory (2020) preferably includes a genre server handler (2030) (discussed in more detail with reference to figures 3 and 4) which contains a

a debate); an initial state being conditions present prior to start of genre instance;
interaction rules as applied to each genre instance; and enforcement rules which are
applicable when a participant violates the interaction rules.

These definitions can be stored as simple text files, each section delimited by the
name of the section with the entries for each preceded by a tab character. Those skilled
in the art will appreciate that other data structures and representations could be used as
well. Those skilled in the art will also appreciate that genre definitions can include
additional headings such as access control restrictions, or types of questions a speaker is
allowed to answer.

As an example, the definition for a lecture genre is listed:

Title

Basic Lecture

Roles

Required: Speaker

Default: Spectator

Other:

Initial State

Presentation_period

Interaction Rules

IF (Presentation_period OR Q&A_period) THEN (can_post Speaker)

**IF (posting = "Any questions?") THEN (Q&A_period) AND
(NOT Presentation_period)**

IF (Q&A_period) THEN (can_post Spectator)

Enforcement Rules

IF (poster == Spectator) AND (NOT Q&A_period) THEN (Interruption)

IF (Interruption) THEN (increment interrupt_count)

**IF (Interruption) THEN (send_message "Don't interrupt! Wait for Q&A
period")**

IF (interrupt_count > 10) THEN (disconnect)

This genre, entitled "Basic Lecture," specifies that there is one required role: **Speaker**, and one default role: **Spectator**. Impliedly, any user other than the speaker that joins a given instance of this genre is assigned the role of Spectator. Initially, instances of this genre begin with Presentation_period (a flag) being true. The enforcement and

5 interaction rules are each checked, respectively, each time there is a posting to a genre instance. For this instance, the interaction rules for Basic Lecture stipulate that Speaker can post both when Presentation_period and Q&A_period are true, but that any Spectator can only post when Q&A_period is true. They also specify that Q&A_period becomes true and Presentation_period false when "Any questions?" is posted. Also for this

10 instance, the enforcement rules stipulate that an interruption has occurred if a Spectator posts when Presentation_period is true. The enforcement rules also specify that whenever Interruption is true, that the poster's interrupt_count is to be incremented. Those with ordinary skill in the art will appreciate that this could be accomplished by modifying a interrupt_count field in the user's entry in the user database (2080). Also,

15 when Interruption is true, the user who made the offending post is sent the message: "Don't interrupt! Wait for Q&A period," and, if the offending user's interrupt_count is above 10, they are disconnected. Those with ordinary skill in the art will appreciate that methods for sending a given user a warning message include but are not limited to posting the message within the current application (e.g., if Lou is the interrupter, by

20 posting "Lou: Don't interrupt! Wait for Q&A period."), or by sending the message via e-mail. Those with ordinary skill in the art will also appreciate that a given user's interrupt_count could be checked by retrieving it from the user's entry in the user database (2080).

According to a preferred embodiment of the present invention, the initial state includes a description of the graphic representation of the genre with the interaction and enforcement rules specifying how changes in the state of a given instance are represented. For example the initial state of a genre could indicate that a geometric shape
5 will be used for the representation with colored dots - one per active user - positioned to represent interactivity. Examples with further descriptions are given with reference to figures 10 through 13.

According to the present invention, an interaction rule specifies how the graphic representation of the genre instance should change in response to specified conditions.
10 For example, it is specified that the dot representing a user who has just posted should change position to indicate the user's action. Similarly, an enforcement rule specifies how the graphic representation should change to indicate the triggering of an enforcement rule (e.g., the dot representing a given user becomes larger, or surrounded by a jagged line to indicate that the user has just interrupted someone).

15 According to a preferred embodiment of the invention, the effect of triggering an enforcement rule includes preventing the offending user from future participation. This is implemented by modifying a given user's user database (2080) entry to indicate that the user is not allowed to connect. Such an entry modification is also used to block the user from participating for a particular period of time (e.g., a week). A given user can
20 also be blocked from making any sort posting through a similar sort of user database (2080) entry modification. The blocking is implemented by executing a given genre interactions rule and checking that no user who had their **Not_allowed_to_post** field set

in the user database (2080) entry is permitted to post, this field (i.e.,
Not_allowed_to_post) having been set as the result of a past triggering of an enforcement
rule.

A genre interaction handler (2070) according to the present invention updates that
5 state of a given operational genre instance in response to user input using the instance
genre interaction and enforcement rules. Note that both genre instance handler (2060)
and genre interaction handler (2070) access and store state information in the genre
instance database (2090). The genre interaction handler (2070) takes each user input it
receives and compares it to the antecedents of all of the current genre instance's
10 interaction and enforcement rules (e.g., **(poster == Spectator) AND (NOT**
Q&A_period)), executing the consequences (e.g., modifying the graphic representation
of the user in response to a legal action they have made, or disconnecting a user in
response to triggering of an enforcement rule). Those ordinarily skilled in the art will
appreciate that the genre instance handler (2070) can also receive input regarding the
15 passage of time (e.g., input sent as the result of a timeout). Thus, both interaction and
enforcement rules can contain antecedents which include time (e.g., "more than 4
minutes"). Those with ordinary skill in the art will further appreciate that in addition to
making updates to the instance database (2090) to indicate changes in the state of a given
genre instance, the genre interaction handler can also perform other sorts of actions,
20 including but not limited to: disconnecting a given user; sending a message to one or
more users (e.g., using e-mail); updating a given user's user database (2080) entry (e.g.,
to indicate that they have made yet another interruption); barring a user from future

connections for a specified period of time; and barring a user from making postings for specified period of time.

Figure 3 depicts an example of the genre server's logic, which is a module having stored codes executable by CPU 2000 to operate the server. As shown, the server waits for input in 3000. The input is checked in step 3010 for genre service interaction, and if the genre system is involved, then, in step 3030, the genre server handler (2030) is invoked; otherwise a miscellaneous handler is invoked in step 3020. Those with ordinary skill in the art will appreciate that the checking process in step 3010, can be effected by identifying which TCP/IP port the server was contacted on. See, Douglas Comer, **Internetworking with TCP/IP, Vol. 1 Principles, Protocols and Architecture.** Prentice Hall, Englewood Cliffs, New Jersey, 1991. Following the completion of either handler, i.e., steps 3020 or 3030, the flow continues at step 3000, where the server (1010) waits for input.

Figure 4 illustrates a representative flow of the genre server handler (2030) in handling client applications and to enable respective users to interact via the genre system. As shown, in step 4000 the registration handler (2040) is called to authorize the user making the request. If it returns "no," the genre handler (2030) exits in step 4070. Otherwise, the request is checked to see whether the user wants to define a new genre in step 4010. The registration handler will be further described with reference to figure 5. If the user is to define a new genre, the genre definition handler (2050) is invoked in step 4020 to handle definitions input by the user. After which the genre handler exits in step 4070. If the request is not to define a new genre, then in step 4030 the request is checked

to see whether the user wants to create or modify an instance of a genre. If so, the genre instance handler (2060) (further described with reference to figure 6) is invoked in step 4040 to handle modifications input by the user. After execution of the modification, the genre server handler (2030) exits in step 4070. Otherwise, in step 4050, the request is
5 checked to see whether it involves an interaction in one of the operational genre instances. If not, the genre server handler (2030) exits in step 4070. If so, the genre interaction handler (2070) is invoked in step 4060 to facilitate interaction by the user in the operational genre instances. After whose operation, the genre server handler (2030) exits in step 4070.

10 The registration handler (2040) determines whether to allow a given user access to the genre server handler (2030). Referring to Fig. 5 in step 5000, the handler first checks whether the given user is already connected to the server by consulting the user's entry in the user database (2080) to see whether they are marked as being currently
15 connected; if so, the handler returns yes in step in 5010. If the user is not already connected, then, in step 5020, the registration handler (2040) checks to see whether the given is permitted to connect. This determination can also be made by consulting the user database (2080), wherein prohibitions to enter can be found in flags associated with the user in the user database. Grounds for denial can include, but are not limited to, a
20 missing entry in the database, such as user has not signed up or paid their membership fee; user's entry indicates that he is not allowed to connect for some specified period of time (e.g., as a penalty for violating genre rules during a prior usage of the system). If the given user is not allowed to connect, then the registration handler (2040) returns no in step 5030. If the user is allowed to connect, then they must pass an authorization

challenge in step 5040. According to a preferred embodiment of the present invention, this challenge prompts the user to specify the user ID and password and the ID and password is compared against stored information in the user's user database (2080) entry. If the user does not pass this authorization, then the registration handler returns no in step 5030. Otherwise, the user is marked as being connected in the user database (2080) in step 5050, and yes is returned in step 5060.

Preferably, a session key is assigned to the user's connection and used to indicate that the user is being connected. This would enable a given user to participate in multiple genre instances on the same server (1010) simultaneously.

Figure 6 depicts an exemplary process of the genre instance handler (2060), which is an interface providing access to genre instances for network-connected clients. The genre instance handler (2060) preferably allows connected clients to add (e.g., create new instances of a given genre); delete (e.g., remove existing genre instance); modify (e.g., add one or more new rules to those of the current genre instance); update the base genre definition (e.g., if two new enforcement rules were added, updating the definition of "Basic Lecture" to include the two rules.); and swap the base genre of a given instance (e.g., switching the instance genre from "Basic Lecture" to "Debate.").

As shown, in Fig. 6, the request is checked to see whether the user wants to create a new instance of a genre. If so, in step 6010 the user selects one of the existing genres from the genre database (2100). Note that the user can at his option create a new genre each he connects using the genre definition handler (2050). Once selected and retrieved from the genre database (2100), the user can specify bindings between user ID and

After storing the new instance in the instance database (2090), the genre instance handler (2060) exits in step 6170.

If the request is not one to add to a new instance, step 6040 checks whether it is a request to switch the genre of the current instance. If so, in step 6050 the user selects a new genre from the genre database (2100). Note that if the genre the user wants is not already in the genre database (2100), then the user can define it using the facility provided by the genre definition handler (2050) as discussed above. Once retrieved from the genre definition database (2100), in step 6060 the user specifies all required parameters, which include bindings between the participants of the current instance and the roles of the new genre, especially any required roles. Preferably, the new instance includes the session ID of the current instance assigned to it. In step 6070, the new genre

instance is added to the instance database (2090); and in step 6080 the current instance is deleted. Then, in step 6170, the genre instance handler (2060) exits.

If the request was not to switch the genre of the current instance, then step 6090 checks whether the user wants to modify the current instance in some other way. If so, then in step 6100 the user makes whatever changes he wishes. These changes could include modifications to any of the data describing the current instance (e.g., adding a new interaction rule or modifying enforcement rules or penalties). Preferably, the information concerning a given genre instance is expressed by a text file. Any changes a user wishes to make to a given genre instance can be made simply by modifying the text file describing the instance. In step 6110, the given genre instance's database entry is updated in the instance database (2090) (e.g., overwriting the current instance description file with the newly modified one). Then, in step 6170, the genre instance handler (2060) exits.

If the request is not to modify the genre instance, the request is checked to see in step 6120 whether it is to update the genre definition of the current instance's genre. If so, in step 6130, all data relevant to the genre definition is extracted from the current state information of the genre instance. A preferred implementation includes: a list of the required roles, the default role (if any), a list of other roles, a description of the initial state, a list of interaction rules, and a list of enforcement rules. In step 6140, the genre's definition is updated in the genre database (2100); and in step 6170 the genre instance handler (2050) exits.

the Java programming language. See Gary Cornell and Cay Horstmann **Core Java**, second edition, SunSoft Press, A Prentice Hall Title, Mountain View, CA. 1997, ISBN 0-13-596891-7. On personal data assistants (**PDA**), like that sold under the trademark WorkPad by IBM, GUIs can be developed in the C programming language, using the graphic libraries supplied by Palm Computing.

The content of the client's user display is preferably created by the software running on the client (1020 - 1060), based on non-graphic data sent by the server (1010). The client (1020 - 1060) may add another colored dot to the graphical representation of the current genre instance in response to a message from the server (1010) such as "new spectator 'Roxanne' joins.". Alternatively, the server may send to the client the full graphic representation, in BMP or equivalent format, which the client (1020 - 1060) simply projects onto its display (7000). Other versions of presentation to the display known to one ordinarily skilled in the art and within contemplation of the present invention.

Figure 8 depicts an exemplary flow process of the genre client's logic. As shown, in step 8000, the client waits for input - both remote input from the network via the network interface (7010), and local input from the user via the input (7020) or pointing (7030) devices. In step 8010, the client determines whether the input is related to the genre application; if so, the client sends the input to the genre client handler (7060) in step 8030; if not, the client sends other inputs to other miscellaneous handlers in step 8020. Following the completion of steps 8020 or 8030, the logic continues waiting for input at step 8000.

Figure 9 shows an exemplary flow of process executed by the genre client handler (7060). The software module genre client logic running the client (1020-1060) communicates with the server (1010) via the network (1000) to enable the end-user to communicate with other operationally connected users. As shown, input at the genre client handler is checked to see whether it is information from the server (1010) in step 9000; if it is, the state or display of the client application are updated using this information. Examples include the posting of messages from other users and the update of the graphic representation of the user's current genre instance. Once updated, the genre client handler (7060) exits in step 9050. If the input is not from server 1010, the input is checked whether it is a request for local service from the end user in step 9020. Such requests may include, but are not restricted to, requests from the end user for the user ID associated with a given iconic representation. For example, a client may ask "Who is associated with the red dot?", requested by the user double-clicking his mouse when the cursor is pointing to the red dot. If the request is local, then in step 9040, the request is fulfilled, following which the handler (7060) exits in step 9050. Otherwise, the request is treated as one which must be sent to the server. This involves translating the request, if necessary, and sending the data to the server. Exemplary requests include the user sending a posting to the current genre instance. For example, a question (in text), by typing the text while the cursor of the user's GUI is position in a text entry area; the user sending a request, for example, user signaling that she wants to ask a question when possible, by double clicking a button marked "Question" in their GUI; the user dragging and dropping the icon which represents him to a particular area in the graphic representation of the current genre instance, by moving one's icon from the pro to the

against area in the graphic representation of a debate; the user requesting a modification of the current genre instance, including modifying its parameters, such as specifying a new rule for the current genre instance, or deleting it, by double clicking a button marked "Modify current genre instance," and then making the relevant mouse clicks or keystrokes; the user requesting a modification to the definition of the current genre instance's genre, such as by overwriting the definition of the Basic Lecture genre to include the new rules that have been added to the current instance of the Basic Lecture genre. This may be implemented by double clicking a button marked "Modify current genre definition" and then making the relevant mouse clicks or keystrokes; the user requesting to leave the current genre instance, by double clicking a button marked "Leave current genre instance"; the user requesting to join an existing genre instance or create a new genre instance, by double clicking a button marked "Join instance" or "Create instance", respectively, and then making the relevant mouse clicks or keystrokes; the user requesting to modify, delete or add a new genre definition, such as by double clicking a button marked "Modify genre definition", "Delete genre definition", or "Add genre definition", respectively, and then making the relevant mouse clicks or keystrokes.

The following descriptions are directed to examples of genres, including descriptions of specialized graphic representations for each genre. Figures 10 and 11 depict an example of the graphic representation of a lecture genre. As shown in Figure 10, the lecture is represented by the pie slice 10000, the speaker by the colored dot 10040, and the spectators by the colored dots 10010, 10020, and 10030. The initial state - how instances of this genre begin - include the steps of: (1) the lecture is represented by the pie slice; (2) the speaker is located at the tip of slice, and (3) all of the spectators

are located back at the curved edge. The default role for this genre is that of spectator, meaning that anyone who joins an instance of this genre is made a spectator and positioned back on the curved edge of the slice. In general, in this graphic representation of a lecture, the more a user speaks, the further towards the tip of the slice the user move, such as seen in Figure 11. Here the pie slice 11000 contains 5 dots 11010 - 11050. One of these dots, 11040, represents a user who has just joined the genre instance and, so is positioned on the curved edge. One of the other dots, 11010, represents a spectator that has asked a question, and, so, his dot has moved towards the point to represent this posting.

Those with ordinary skill in the art will appreciate that graphically, dot 11040 as a new user can be indicated simply by a different color from the other dots, and each dot representing a different user can also be indicated by each dot having a different shape or letter.

This graphical representation also provides a way to represent a given user speaking out of turn. As shown, a jagged line 11060 encircles dot 11010 to indicate that dot 11010's user spoke out of turn. Those skilled in the art will appreciate that the size or brightness of the icon representing a given user can be increased each time he interrupts, allowing other participants to see how many times the given user has interrupted in the current instance. Those skilled in the art will also appreciate that other qualities of a given user - e.g., how many times they have interrupted in the past could also be depicted, the information retrieved from the user database (2080) while in the process of generating an icon for the user.

Figure 12 shows an example of a graphic representation of a debate genre. As shown, each instance is represented by a rectangle (12000) which is divided into three regions: For (12010), Undecided (12020), and Against (12030), each corresponding to the 3 possible states of mind of the participants; Undecided being the default. All new comers to instance of this type of genre are positioned in the undecided area (12020). Figure 12 shows five current users, depicted by dots 12040, 12050, 12060, 12070, and 12080. As shown, the users represented by dots 12040 and 12050 are arguing for the current debate topic; with the users represented by dots 12070 and 12080 arguing against; dot 12060's user not having made up her mind yet. Note that if a new user joined this genre instance, his dot would be positioned in the Undecided area. To change argument teams, all a user needs to do is to drag and drop her icon into the desired team's region. E.g., to join the For team, dot 12060's user need only drag and drop his dot into the For region (12010). This request - translated from the graphic commands - would be sent from the user's client to the server (1010), which in turn, would update the state of the genre instance and then broadcast this new state to all operationally connected users.

Figure 12 also depicts a square (12090) around dot 12070. This is a graphic means of indicating that it is now dot 12070 user's turn to speak. The jagged edge (12100) around dot 12050 indicates that dot 12050's user (i.e., the user represented by dot 12050) has spoken out of turn.

This graphic representation also has a means of indicating how much a given user has spoken, preferably by positioning the dot closer to the Undecided region (12020) the more the given user has spoken. Thus, as shown, the users represented by dot 12040 and

12080 have spoken little, if at all; while the users represented by dots 12050 and 12070 have spoken a fair amount, and nearly the same as each other.

Those with ordinary skill in the art will appreciate that the definition of this type of genre can include rules indicating that turns will be allocated so that the turn to speak alternates back and forth between the For and the Against teams. An enforcement rule could specify a maximum post length after which a given post is truncated. Overly long postings could also result in some graphic display, such as a modification to the speaker's dot, e.g. an "X" printed across it.

Figure 13 depicts an example of a graphic representation of a roundtable discussion, such as a discussion in which each and every participant is supposed to speak, usually one after the other in rotation. As shown, the graphic representation includes a circle divided into sections (13000), one for each user, who is represented by a dot (13010 through 13050). The box (13060) around dot 13020, indicates that is dot 13020 user's turn to speak. The jagged line (13070) around dot 13050 indicates that the user represented by dot 13050 has spoken out of turn. This graphic representation also has a means of indicating how much a given user has spoken, preferably by positioning user dots closer to the center the more the given user has spoken. Thus, as shown, the users represented by dot 13010 and 13030 have spoken little, if at all; while the users represented by dots 13020, 13040 and 13050 have spoken a fair amount, and nearly the same as each other.

Those with ordinary skill in the art will appreciate how similar graphic representations can be used to exploit the present invention to support genres which

include, but are not limited to: a personal office which an area owned by one user in which visitors come and talk - mostly to the office owner; a court room interaction genre, having a judge, defendant, plaintiff, defending and prosecuting attorneys, witnesses, jury, and spectators; and a help line with help requesters and providers with preferred

5 embodiments of the present invention having been described. Alternatives, various modifications and improvements will occur to those skilled in the art. Thus, the detailed description should be understood as an example and not as a limitation. The proper scope of the invention is properly defined by the appended claims.

What is Claimed is:

1. A method of user-defined structured interaction online, comprising the steps of:

defining an interaction genre;

5 creating an operational instance of the genre, said instance being initialized to a predetermined state;

monitoring input from online users operatively connected to said instance;

updating a state of the instance and responding to user's requests if said input satisfies a criteria set by the instance's interaction rules; and

10 broadcasting the updated state to all online users operatively connected to the instance.

2. The method of claim 1 wherein the step of defining an interaction genre includes one of copying and modifying a previously defined interaction genre.

3. The method of claim 1 wherein the step of defining an interaction genre
15 includes specifying rules of a graphic representation of the genre, including rules specifying how interactions are represented.

4. The method of claim 3 wherein the graphic representation includes specified symbols representing respective users' roles.

5. The method of claim 3 wherein the graphic representation includes specified distances from references to proportionally represent action or nonaction of users.

5 6. The method of claim 3 wherein the graphic representation includes specified positions representing status of respective users.

7. The method of claim 1 wherein said step of creating an operation instance of a genre includes setting genre parameters.

8. The method of claim 7 wherein said genre parameters include genre roles.

10 9. The method of claim 7 wherein said genre parameters include rule parameters.

10. The method of claim 1 wherein said input includes one of text messages, audio clips and video clips.

15 11. The method of claim 3 wherein said input includes the user's change in roles by dragging and dropping of graphics elements of the graphic representation of the state of the instance.

12. The method of claim 1 wherein said user's requests include requesting to ask a question.

13. The method of claim 1 wherein said user's requests include a request for a clarification.

14. The method of claim 1 wherein said step of monitoring includes monitoring the passage of time between inputs by a user.

5 15. A method of user-defined structured interaction online, comprising the steps of:

defining an interaction genre;

creating an operational instance of the genre, said instance being initialized to a predetermined state;

10 monitoring input from online users operatively connected to said instance;

updating a state of the instance and executing specified actions in response to enforcement rules; and

broadcasting the updated state to all online users operatively connected to the instance.

15 16. The method of claim 15 wherein said step of updating the state of the instance and executing specified actions in response to enforcement rules includes sending the rule violator a message.

20 17. The method of claim 15 wherein said step of updating the state of the instance and executing specified actions in response to enforcement rules includes disconnecting a user violating said rules from the current instance.

18. The method of claim 15 wherein said step of updating the state of the instance and executing specified actions in response to enforcement rules includes barring a user violating said rules from future connections for a specified period of time.

5 19. The method of claim 15 wherein said step of updating the state of the instance and executing specified actions in response to enforcement rules includes modifying an iconic representation of a user violating said rules in a graphic representation of the genre instance.

20. The method of claim 15 wherein said step of updating the state of the instance in response to interaction rules includes changing the genre of the instance.

10 21. The method of claim 20 wherein the graphic representation of the instance is changed in response to the changing of its genre.

22. The method of claim 15 wherein said step of updating the state of the instance includes changing one or more genre parameters including genre roles.

15 23. The method of claim 15 wherein said updating step includes repositioning of the icons representing the operative users.

24. The method of claim 28 wherein said updating step includes modifying icons to represent changes in roles of respective users.

25. The method of claim 1 wherein said step of broadcasting the updated state of the instance includes broadcasting the instance's genre rules.

26. The method of claim 1 wherein said step of broadcasting the updated state of the instance includes broadcasting the instance's genre parameters including role assignments.

5 27. The method of claim 1 wherein said step of broadcasting the updated state of the instance includes the broadcast of the graphic representation of the state of the instance.

28. The method of claim 1, further including the step of identifying a given user by moving a cursor over the icon representing that user.

10 29. A computer-based medium having stored programs readable by a computer for causing the computer to execute method steps for facilitating interaction among a plurality of users operatively connected to the computer, the method comprising the steps of:

receiving requests from the plurality of users to participate in an interactive session;

15 registering said users by storing user identifications and passwords of respective users;

storing said identifications and passwords in a user database;

authorizing said users as participants in the interactive session upon receiving a clearance signal;

20 setting parameters and rules governing the interactive session and informing the participants of the parameters and rules;

monitoring inputs from the participants during the interactive session; and

enforcing penalties upon participants violating said rules.

30. The computer-based medium according to claim 29, wherein said clearance signal is given based on data on users stored in the user database.

31. The computer-based medium according to claim 29, further including the step of modifying said parameters by said participants.

5 32. The computer-based medium according to claim 29, wherein said step of enforcing penalties includes associating violation data with user data of violating participants in the user database.

DISCUSSION

The results of this study indicate that the use of a single, standardized, and validated questionnaire can provide a reliable and valid measure of the prevalence of mental health problems in a community sample. The results also indicate that the use of a single, standardized, and validated questionnaire can provide a reliable and valid measure of the prevalence of mental health problems in a community sample. The results also indicate that the use of a single, standardized, and validated questionnaire can provide a reliable and valid measure of the prevalence of mental health problems in a community sample.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6:




Figure 7




Figure 9

Figure 10







Figure 11



Figures 10 and 11



Figures 12



Figures 13